

§ 78.05-5 Charts and nautical publications.

As appropriate for the intended voyage, all vessels except barges, ferryboats and vessels operating exclusively on rivers, must carry adequate and up-to-date—

- (a) Charts;
- (b) Sailing directions;
- (c) Coast pilots;
- (d) Light lists;
- (e) Notices to mariners;
- (f) Tide tables;
- (g) Current tables; and
- (h) All other nautical publications necessary.¹

[CGD 75-074, 42 FR 5963, Jan. 31, 1977]

Subpart 78.07—Notice and Reporting of Casualty and Voyage Records**§ 78.07-1 Notice and reporting of casualty and voyage records.**

The requirements for providing notice and reporting of marine casualties and for retaining voyage records are contained in part 4 of this chapter.

[CGD 84-099, 52 FR 47535, Dec. 14, 1987]

Subpart 78.10—Persons Allowed in Pilothouse and on Navigation Bridge**§ 78.10-1 Persons excluded.**

Masters and pilots shall exclude from the pilothouse and navigation bridge while underway, all persons not connected with the navigation of the vessel. However, licensed officers of vessels, persons regularly engaged in training, regulating, evaluating or learning the profession of pilot, officials of the United States Coast Guard, United States Navy, United States Coast and Geodetic Survey, United States Army Corps of Engineers, Maritime Administration, and National Transportation Safety Board may be allowed in the pilothouse or upon the navigation bridge upon the responsibility of the master or pilot.

[CGD 91-023, 59 FR 16779, Apr. 8, 1994]

¹For United States vessels in or on the navigable waters of the United States, see 33 CFR 164.33.

Subpart 78.12—Stability Information**§ 78.12-1 Posting of stability letter.**

If a stability letter is issued under § 170.120 of this chapter, it must be posted under glass or other suitable transparent material in the pilothouse of the vessel.

[CGD 79-023, 48 FR 51007, Nov. 4, 1983]

Subpart 78.13—Station Bills**§ 78.13-1 Muster lists, emergency signals, and manning.**

The requirements for muster lists, emergency signals, and manning must be in accordance with subchapter W (Lifesaving Appliances and Arrangements) of this chapter.

[CGD 84-069, 61 FR 25288, May 20, 1996]

Subpart 78.15—Doors Closed at Sea**§ 78.15-1 Subdivision bulkheads.**

(a) All watertight doors in subdivision bulkheads shall be kept closed during navigation except when necessarily opened for working of the vessel, and in such cases they shall always be ready to be immediately closed.

Subpart 78.16—Port Lights**§ 78.16-1 General.**

If port lights are fitted in spaces used alternatively for the carriage of cargo or passengers as permitted by § 171.116(d) of this chapter, dead covers must be fitted on the port lights when cargo is carried.

[CGD 79-023, 48 FR 51007, Nov. 4, 1983]

Subpart 78.17—Tests, Drills, and Inspections**§ 78.17-1 Application.**

(a) Except as specifically noted, the provisions of this subpart shall apply to all vessels.

§ 78.17-3 Watertight doors.

(a) It shall be the duty of the master to see that all watertight doors in subdivision bulkheads that may be opened